

Shaft collars two-piece

Item description/product images



Description

Material:

Steel 1.0718
Stainless steel 1.4305.
Aluminium.

Version:

Steel black oxidised, screw steel 12.9.
Stainless steel bright, screw stainless steel A2-70.
Aluminium bright, screw stainless steel A2-70.

Note:

Two-piece shaft collars surround the shaft with a uniformly distributed clamping force. This leads to a dimensionally precise fit and very high retaining forces without damaging the shaft.

The shaft tolerance should lie within h11.

Two-piece shaft collars can be quickly and easily mounted or removed without dismantling other components.


Temperature range:

-40 °C to +175 °C.

On request:

Other dimensions.

Drawings



Overview of items

Shaft collars two-piece

Order No.	Main material	Steel code	B	C (DIN 912)	D1	D2	R
K0612.00401	steel	-	9	M3x8	4	16	20,7
K0612.00501	steel	-	9	M3x8	5	16	20,7
K0612.00601	steel	-	9	M3x8	6	16	20,7

Shaft collars two-piece

Overview of items

Order No.	Main material	Steel code	B	C (DIN 912)	D1	D2	R
K0612.00801	steel	-	9	M3x8	8	18	22,4
K0612.01001	steel	-	9	M3x10	10	24	26
K0612.01201	steel	-	11	M4x12	12	28	31,8
K0612.01501	steel	-	13	M5x16	15	34	39,4
K0612.01601	steel	-	13	M5x16	16	34	39,4
K0612.01801	steel	-	13	M5x16	18	36	41,1
K0612.02001	steel	-	15	M6x18	20	40	46,4
K0612.02201	steel	-	15	M6x18	22	42	48,1
K0612.02501	steel	-	15	M6x18	25	45	50,8
K0612.02801	steel	-	15	M6x18	28	48	53,7
K0612.03001	steel	-	15	M6x18	30	54	58,6
K0612.04001	steel	-	15	M6x18	40	60	65
K0612.05001	steel	-	19	M8x25	50	78	87
K0612.00402	stainless steel	1.4305	9	M3x8	4	16	20,7
K0612.00502	stainless steel	1.4305	9	M3x8	5	16	20,7
K0612.00602	stainless steel	1.4305	9	M3x8	6	16	20,7
K0612.00802	stainless steel	1.4305	9	M3x8	8	18	22,4
K0612.01002	stainless steel	1.4305	9	M3x10	10	24	26
K0612.01202	stainless steel	1.4305	11	M4x12	12	28	31,8
K0612.01502	stainless steel	1.4305	13	M5x16	15	34	39,4
K0612.01602	stainless steel	1.4305	13	M5x16	16	34	39,4
K0612.01802	stainless steel	1.4305	13	M5x16	18	36	41,1
K0612.02002	stainless steel	1.4305	15	M6x18	20	40	46,4
K0612.02202	stainless steel	1.4305	15	M6x18	22	42	48,1
K0612.02502	stainless steel	1.4305	15	M6x18	25	45	50,8
K0612.02802	stainless steel	1.4305	15	M6x18	28	48	53,7
K0612.03002	stainless steel	1.4305	15	M6x18	30	54	58,6
K0612.04002	stainless steel	1.4305	15	M6x18	40	60	65
K0612.05002	stainless steel	1.4305	19	M8x25	50	78	87
K0612.00404	stainless steel	1.4404	9	M3x8	4	16	20,7
K0612.00504	stainless steel	1.4404	9	M3x8	5	16	20,7
K0612.00604	stainless steel	1.4404	9	M3x8	6	16	20,7
K0612.00804	stainless steel	1.4404	9	M3x8	8	18	22,4
K0612.01004	stainless steel	1.4404	9	M3x10	10	24	26
K0612.01204	stainless steel	1.4404	11	M4x12	12	28	31,8
K0612.01504	stainless steel	1.4404	13	M5x16	15	34	39,4
K0612.01604	stainless steel	1.4404	13	M5x16	16	34	39,4
K0612.01804	stainless steel	1.4404	13	M5x16	18	36	41,1
K0612.02004	stainless steel	1.4404	15	M6x18	20	40	46,4
K0612.02204	stainless steel	1.4404	15	M6x18	22	42	48,1
K0612.02504	stainless steel	1.4404	15	M6x18	25	45	50,8
K0612.02804	stainless steel	1.4404	15	M6x18	28	48	53,7
K0612.03004	stainless steel	1.4404	15	M6x18	30	54	58,6
K0612.04004	stainless steel	1.4404	15	M6x18	40	60	65
K0612.05004	stainless steel	1.4404	19	M8x25	50	78	87
K0612.00403	aluminium	-	9	M3x8	4	16	20,7
K0612.00503	aluminium	-	9	M3x8	5	16	20,7
K0612.00603	aluminium	-	9	M3x8	6	16	20,7
K0612.00803	aluminium	-	9	M3x8	8	18	22,4
K0612.01003	aluminium	-	9	M3x10	10	24	26
K0612.01203	aluminium	-	11	M4x12	12	28	31,8
K0612.01503	aluminium	-	13	M5x16	15	34	39,4
K0612.01603	aluminium	-	13	M5x16	16	34	39,4
K0612.01803	aluminium	-	13	M5x16	18	36	41,1
K0612.02003	aluminium	-	15	M6x18	20	40	46,4
K0612.02203	aluminium	-	15	M6x18	22	42	48,1
K0612.02503	aluminium	-	15	M6x18	25	45	50,8
K0612.02803	aluminium	-	15	M6x18	28	48	53,7
K0612.03003	aluminium	-	15	M6x18	30	54	58,6
K0612.04003	aluminium	-	15	M6x18	40	60	65
K0612.05003	aluminium	-	19	M8x25	50	78	87

